

AMPURE

Ampure Go™ Gen 2

Portable Level 2 EV Cordset



Key Features

- UL certified according to established regulatory bodies
- Interchangeable grid plugs for North America
- Customized branding and/or styling options
- State-of-the-art safety features
- Compact, portable Level 2 Charger
- 3 LED light indication for easy charging status read out
- IP67 Rating can be submerged up to 3ft (1m)
*Excluding Grid Plugs (IP55 Rating)
- Easy to use, take it anywhere, simply plug-in and charge
- Designed and engineered in California, USA

Technical Specifications

Voltage	120 - 240 VAC
Power	12 A @ 120 V to 32 A @ 240 / 208 V
Circuit Breaker Rating	15 A @ 120 V to 32 A @ 240 / 208 V
Frequency	45-65Hz
Grid Plug Types	NEMA 14-50 & NEMA 5-15
Cable Length	20 ft (6.1 m)
Weight	9 lbs. (4.1 kg) w/ two Grid ASM
Operating Temperature	-40°F (-40°C) to 185°F (+85°C)
Enviornmental Rating	IP67 / NEMA watertight
Coupler Type	NACS
Certifications	UL, cUL, and FCC
HMI	3 LED Status Bar

Ampure
1333 S. Mayflower Ave Suite 100
Monrovia, CA 91016 USA
Hotline: +1 888-833-2148 (UNITED STATES)

